

Stackable High Voltage Lithium Battery

SAS51100-HV

51.2V 100Ah

LFP Battery



PRODUCT FEATURE



HIGH CYCLE LIFE

Can achieve 6000 cycles at 90% state of charge, effectively reducing total cost of ownership.



FAST CHARGING SPEED

High charge and discharge efficiency, reducing equipment downtime and saving more time.



HIGHLY ADAPTABLE

Strong environmental adaptability, can withstand up to 60°C.



SAFER

Real-time monitoring of PDU for better system protection.



EASY TO STORE

Due to its extremely low self-discharge rate (LSD) and no risk of sulfation, it can last up to 6 months.



EASY TO STORE

Lithium batteries provide more watt-hours per kilogram while weighing only one-third of their SLA equivalents.



Email: info@sailsolarpv.com Web: www.sailsolarpv.com www.sailsolares.com
Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

Rechargeable LITHIUM IRON PHOSPHATE (LiFePO4)Battery

DATASHEET

MODEL

Battery Type	LiFePO4
Nominal Battery Energy	5.12kWh
Nominal Capacity	100Ah
Nominal Voltage	51.2V
Net Weight	40.8kg
Dimension(W/D/H)	482*475*133mm
Communication	RS232/RS485/CAN/BLUETOOTH/WIFI
Cycle Life*	6000 cycles 80% DOD,0.5C
Protection Level	IP20
Expansion	Up to 15 units in series
Compatible Inverters	Deye/GoodWe/Solis/SAJ/Sinexcel/Hoymiles/Growatt/Ecatus/Sermatec/ATESS/Sunways etc.

Certification & Safety Standard UN38.3, MSDS, IEC62161, CE, UL1973, UL2054

Stackable Type	SAS-20.48kWh-Z	SAS-25.6kWh-Z	SAS-30.72kWh-Z	SAS-35.84kWh-Z
Battery Module Quantity	4units	5units	6units	7units
Nominal Battery Energy	20.48kWh	25.6kWh	30.72kWh	35.84kWh
Nominal Capacity	100Ah	100Ah	100Ah	100Ah
Nominal Voltage	204.8V	256.0V	307.2V	358.4V
Max.Power Output	20.48kW	25.6kW	30.72kW	35.84kW
Discharge Cut-off Voltage	176V	220V	264V	308V
Charge Cut-off Voltage	227.2V	284V	340.8V	397.6V
Recommend Charging Current	50A	50A	50A	50A
Recommend Discharging Current	50A	50A	50A	50A
Max Charge/Disharge Working Current (A)	100A	100A	100A	100A
Net Weight	160.8kg	204kg	244.8kg	285.6kg

Working temperature Charge : 0 ~ 55°C / Discharge : -20°C ~ 55°C

Design Life 10 years+

*File version: 2026V1-EN

*Weight and Size of the battery module is based on the actual product,

*Specifications may vary during continuous improvements, pls contact us for latest details.

*The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

*Each column can hold a maximum of 6 batteries plus one high-voltage box, please confirm the number of batteries per column with the sales team.

